



2009 Figure 8 Rules

If these rules do not say you can do it then don't do it! All interpretations by the track are final. You are responsible to know the track's position on all rules. **IGNORANCE IS NO EXCUSE!**

1. Car may be any stock front clip car, rest of car may be fabricated. Wheelbase 105" Min.
2. Minimum 4" ride height.
3. Weight minimum of 3,200 lbs with original driver.
4. Numbers on roof and both doors. Minimum 18" high, 3" thick.
5. Lettering and numbers must be in a contrasting color to paint scheme of car. No obscene language or gestures painted on car or on decals.
6. Body Optional (stock or fabricated)
7. 8" steel rims, any 8" treaded tire (No Recaps).
8. Any stock type rear end. Quick change Okay. No aluminum tubes. No wide 5 hubs. No cambered tubes.
9. Any shock (No coil overs)
10. Any steering (Rack & Pinion Okay)
11. Transmission optional (Must have scatter shield). No internal clutch transmissions. No in and out boxes.
12. Engines location - #1 cylinder lined up with ball joint.
13. Engine - Flat top motor, any flat tappet cam. (No roller cams) Roller Rockers Okay.
14. Any cast iron head - valve size max. 2.02 - max 1.6. No porting or polishing. 170 cc intake port size.
15. Stock type clutch (No mini clutches) 10" min.
16. Stock Flywheel - L88 Okay.
17. Carburetor - 2 barrel or Q-jet.
18. Any aluminum intake (No Botties)
19. Any stock type H.E.I. ignition.
20. Suspension - Stock type lower A frames.
21. May run tubular uppers - front spindals optional (No drop spindals).

The track reserves the right to add weight at its discretion for the fairness of competition.
READ THE GENERAL RULES !!!!